## AMENDMENTS TO THE CLAIMS

Please amend the claims as indicated hereafter.

 (Original) A method for reducing CPU loading in a software receiver for a packet based communications system comprising the steps of:

measuring the current CPU load:

determining that the CPU load has exceeded a predetermined threshold;

signaling the communications system transmitter to inhibit packet transmission when the threshold is exceeded:

monitoring the CPU load while the transmitter is inhibited:

determining that the CPU load has fallen below a predetermined threshold; and

- signaling the communications system transmitter to begin transmitting packets once the CPU load has fallen below the predetermined threshold
- (Original) A method as in claim 1, wherein the measurement of CPU loading is made by an operating system background task.
- (Original) A method as in claim 1, wherein the CPU load measurement is based on the response time of the host CPU to a request for interrupt.
- (Original) A method as in claim 1, wherein the transmitter signaling is done through a power save mode.

- (Original) A method as in claim 1, in which the communications system is wireless.
- (Original) A method as in claim 1, in which the communications system is IEEE 802.11 wireless local area network (WLAN).
- (Original) A method as in claim 1, in which the communication system is Bluetooth.
- (Original) A method as in claim 1, in which the communications system is IEEE 802.15 wireless personal area network (PAN).
- 9.-14. (Canceled).